



(43) International Publication Date
9 June 2005 (09.06.2005)


PCT

(10) International Publication Number
WO 2005/051543 A1

- | | | |
|---|--------------------------------------|---|
| (51) International Patent Classification ⁷ :
G01N 35/10 | B01L 3/02, | (71) Applicant (for all designated States except US): GILSON S.A.S. [FR/FR]; 19, avenue des Entrepreneurs, BP 145, F-95400 Villiers-le-Bel (FR). |
| (21) International Application Number: | PCT/IB2004/003876 | (72) Inventors; and
(75) Inventors/Applicants (for US only): VIOT, Francois [FR/FR]; 38 rue des Ruelles, F-95430 Auvers sur Oise (FR). MAY, Yves [FR/FR]; 6B rue de la Ceinture, F-78000 Versailles (FR). |
| (22) International Filing Date: | 24 November 2004 (24.11.2004) | |
| (25) Filing Language: | English | (74) Agent: BELL, Callie, M.; Foley & Lardner LLP , 150 East Gilman Street, Post Office Box 1497, Madison, WI 53701-1497 (US). |
| (26) Publication Language: | English | |
| (30) Priority Data: | | (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, |
| 0313920 | 27 November 2003 (27.11.2003) | FR |
| 0313921 | 27 November 2003 (27.11.2003) | FR |
| 0402433 | 9 March 2004 (09.03.2004) | FR |
| 0409442 | 7 September 2004 (07.09.2004) | FR |
| 0409438 | 7 September 2004 (07.09.2004) | FR |
| 0409443 | 7 September 2004 (07.09.2004) | FR |
| 10/944,532 | 17 September 2004 (17.09.2004) | US |

[Continued on next page]

(54) Title: SYSTEM AND METHOD FOR PRECISE LIQUID MEASUREMENT IN A LIQUID SAMPLING PIPETTE



(57) Abstract: A device and method are provided for correcting a requested volume of liquid to aspirate/dispense by a liquid handling pipette based on the requested volume and/or a physical condition at the pipette. The pipette includes a piston drive mechanism configured to contact a piston assembly and move a piston rod of the piston assembly within a tip holder thereby causing regulation of an amount of liquid in the tip holder. The method includes selecting a requested volume at a pipette, the requested volume representing the amount of liquid to regulate, calculating a correction volume using a volume characterization, wherein the volume characterization characterizes a difference in the amount of the liquid regulated in the tip holder as a function of the requested volume, and displaying the correction volume to a user of the pipette thereby regulating the requested volume of liquid in the tip holder. The volume characterization is determined using a calibration process.

WO 2005/051543 A1